# MATERIAL SAFETY DATA SHEET

Rev. JAN. 2007 Page 1 of 4

## 1. PRODUCT AND COMPANY IDENTIFICATION

Trade Name: **PLASTI-GRIT**<sup>R</sup> **Type V**Chemical Name: Acrylic - Plexi-glass
Chemical Family: Acrylic Polymer
Formula: Acrylic Polymer/resiSTAT<sup>R</sup>

Composition Materials Co., Inc. –125 Old Gate Lane - Milford, CT 06460 Phone - 203-874-6500 Fax - 203-874-6505

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Acrylic Polymer > 97 ACGIH TLV None CAS #80-62-6 OSHA PEL None

Pigment and Additives < 2 ACGIH TLV None

OSHA PEL None

resiSTAT<sup>R</sup> (anti-static agent) < 1 ACGIH TLV None CAS #002764-13-8 OSHA PEL None

# 3. HAZARDS IDENTIFICATION

Material is granular with no odor.

Avoid creating airborne dust. Avoid ignition sources. Provide ventilation. Avoid breathing dust, or contact with eyes or skin. Spilled material can be slippery and cause falls if walked on.

#### **Potential Health Effects**

**EYE:** Solid or dusts may cause irritation or scratch the surface of the eye.

**SKIN**: Potential slight irritation.

**INGESTION:** May be harmful if swallowed.

**INHALATION**: Potential respiratory tract irritation.

Chronic Health Effects: None known.

#### MSDS - TYPE V ACRYLIC PLASTI-GRIT

Page 2 of 4

Carcinogenicity: NTP: No HMIS NFPA

IARC: No Health 2 2
OSHA: No Flammability 0 0
Reactivity 0 0

### 4. FIRST AID MEASURES

**EYES**: Flush with water for 15 minutes. Consult a physician if irritation develops.

**SKIN**: Wash thoroughly with soap and water. Consult a physician if irritation develops. **INGESTION**: Immediately induce vomiting by giving two glasses of water. Call a

physician.

**INHALATION**: Remove to uncontaminated area - fresh air. Call physician if irritation

persists.

# 5. FIRE FIGHTING MEASURES

#### FLAMMABLE PROPERTIES:

FLASH POINT: N/A

Dust can form explosive mixture with air. Temperatures above 370° C will result in depolymerisation releasing highly flammable methylmethacrylate.

FLAMMABLE LIMITS: N/A LEL: N/A UEL: N/A

**HAZARDOUS COMBUSTION PRODUCTS**: Smoke, Carbon Monoxide, Carbon

dioxide, methyl methacrylate.

**EXTINGUISHING MEDIA**: Foam, Dry Chemical, CO2, Water Fog.

FIRE FIGHTING INSTRUCTIONS: Wear self-contained breathing apparatus with a full

face piece. Also wear full protective clothing.

# **6. ACCIDENTAL RELEASE MEASURES**

Sweep up and place in appropriate disposal container. Spilled material can be a slipping hazard. Eliminate flames, sparks, excessive temperatures and oxidizing agents.

MSDS - TYPE V ACRYLIC PLASTI-GRIT

Page 3 of 4

#### 7. HANDLING AND STORAGE

**HANDLING**: Avoid contact with eyes. Use in a well-ventilated area.

**STORAGE**: Store in closed, properly labeled containers in a cool, ventilated area. Keep away from heat, open flames and oxidizing agents. Do not transfer to unmarked containers.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS**: Mechanical ventilation and local exhaust. Use explosion proof electrical equipment for very high dust levels.

**RESPIRATORY PROTECTION**: Recommend a 3M #8710 Dust and Mist Respirator.

**SKIN PROTECTION**: Use rubber gloves. Wash thoroughly before eating, smoking, Applying cosmetics, etc. Launder work clothing before reuse.

**EYE PROTECTION**: Safety glasses with side shields, goggles and/or a face shield **OTHER PROTECTIVE EQUIPMENT**: If necessary, protective rubber apron, shoes or boots, or TYVEC protective suit with hood.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: N/A
MELTING POINT: N/A
VAPOR PRESSURE: N/A
VAPOR DENSITY: N/A

**SOLUBILITY IN WATER:** Insoluble

**EVAPORATION RATE**: N/A

SPECIFIC GRAVITY (H2O=1): 1.2

**pH**: 4-8

**ODOR**: No Odor

**APPEARANCE**: Granular **COLOR**: Clear or Smoke

#### MSDS - TYPE V ACRYLIC PLASTI-GRIT

Page 4 of 4

#### 10. STABILITY AND REACTIVITY

**CHEMICAL STABILITY**(CONDITIONS TO AVOID):Excessive heat, ignition sources.

**INCOMPATIBILITY**: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: Smoke, Carbon Monoxide, Carbon

Dioxide, Methyl Methacrylate.

**HAZARDOUS POLYMERIZATION:** Will not Occur.

**STABILITY**: Stable

## 11. TOXICOLOGICAL INFORMATION

Very low order of acute toxicity.

#### 12. ECOLOGICAL INFORMATION

Cleaned up material is not known to pose any significant ecological problems. Always comply with Federal, State and Local environmental regulations.

## 13. DISPOSAL CONSIDERATIONS

Dispose as solid waste in sanitary landfill according to Federal, State and Local regulations.

## 14. TRANSPORT INFORMATION

**DOT**: Not Regulated. **NMF CLASSIFICATION**: Class 60 - Item 156200

# 15. REGULATORY INFORMATION

Review OSHA Std. for PPE in 29CFR 1910 Subpart I to ensure proper use for any applicable PPE.

WHMIS CLASSIFICATION: Not Applicable

## 16. OTHER INFORMATION

The information in this MSDS was obtained from sources we believe are reliable. However, it is provided without any representation or warranty, expressed or implied, regarding accuracy or correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.