# **MATERIAL SAFETY DATA SHEET**

Rev. JAN. 2007 Page 1 of 4

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

Trade Name: **PERSTRIP<sup>R</sup> MF Type III** Chemical Name: Thermoset Melamine Formaldehyde Chemical Family:Thermoset Plastics Formula: Melamine/resiSTAT<sup>R</sup>

Composition Materials Co., Inc. - 125 Old Gate Lane - Milford, CT 06460 Phone - 203-874-6500 Fax - 203-874-6505

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Polymerized Melamine Molding Compour CAS #9003-08-1	nd	> 97	7 ACGIH TI OSHA PEL	
Pigment and Additives	<		ACGIH TLV SHA PEL N	
resiSTAT <sup>R</sup> (anti-static agent) CAS #002764-13-8	<	-	ACGIH TLV OSHA PEL	None

### 3. HAZARDS IDENTIFICATION

Material is granular with no odor.

Avoid creating airborne dust. Avoid ignition sources. Provide ventilation. Avoid breathing dust, or contact with eyes or skin. Spilled material can be slippery and cause falls if walked on.

#### **Potential Health Effects**

EYE: Solid or dusts may cause irritation or scratch the surface of the eye.
SKIN: Potential slight irritation.
INGESTION: May be harmful if swallowed.
INHALATION: Potential respiratory tract irritation.
Chronic Health Effects: None known.

COMPOSITION MATERIALS CO., INC. 125 OLD GATE LANE, MILFORD, CT 06460 (203) 874-6500 MSDS - PERSTRIP MF TYPE III Page 2 of 4

Carcinogenicity:NTP:NoHMISNFPAIARC:NoHealth22OSHA:NoFlammability00Reactivity000

#### 4. FIRST AID MEASURES

**EYES**: Flush with water for 15 minutes. Consult a physician if irritation develops.

**SKIN**: Wash thoroughly with soap and water. Consult a physician if irritation develops.

**INGESTION**: Immediately induce vomiting by giving two glasses of water. Call a physician.

**INHALATION**: Remove to uncontaminated area - fresh air. Call physician if irritation persists.

# 5. FIRE FIGHTING MEASURES

#### FLAMMABLE PROPERTIES:

FLASH POINT: N/A

Dust can form explosive mixture with air. Sealed (closed) containers can build up pressure if exposed to heat (fire).

FLAMMABLE LIMITS: N/A LEL: N/A UEL: N/A

**HAZARDOUS COMBUSTION PRODUCTS**: Carbon Monoxide, Nitrous Oxides **EXTINGUISHING MEDIA**: Foam, Dry Chemical, Water, CO<sub>2</sub>, Steam.

**FIRE FIGHTING INSTRUCTIONS**: Wear self-contained breathing apparatus with a full face piece. Also wear full protective clothing.

# 6. ACCIDENTAL RELEASE MEASURES

Sweep up and place in appropriate disposal container. Spilled material can be a slipping hazard. Eliminate flames, sparks, excessive temperatures and oxidizing agents.

#### MSDS - PERSTRIP MF TYPE III

### 7. HANDLING AND STORAGE

- **HANDLING**: Avoid contact with eyes. Use in a well-ventilated area. Avoid creating airborne dust.
- **STORAGE**: Store in closed, properly labeled containers in a cool, ventilated area. Keep away from heat, open flames and oxidizing agents. Do not transfer to unmarked containers.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS**: Mechanical ventilation and local exhaust. Use explosion proof electrical equipment for very high dust levels.

**RESPIRATORY PROTECTION**: Recommend a 3M #8710 Dust and Mist Respirator.

**SKIN PROTECTION**: Use rubber gloves. Wash thoroughly before eating, smoking, applying cosmetics, etc. Launder work clothing before reuse.

**EYE PROTECTION**: Safety glasses with side shields, goggles and/or a face shield **OTHER PROTECTIVE EQUIPMENT**: If necessary, protective rubber apron, shoes or boots, or TYVEC protective suit with hood.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: N/A MELTING POINT: N/A VAPOR PRESSURE: N/A VAPOR DENSITY: N/A SOLUBILITY IN WATER: Insoluble EVAPORATION RATE: N/A SPECIFIC GRAVITY (H<sub>2</sub>O=1): 1.5 pH: 4-8 ODOR: No Odor APPEARANCE: Granular, one or several colors.

#### **MSDS - PERSTRIP MF TYPE III**

# **10. STABILITY AND REACTIVITY**

CHEMICAL STABILITY(CONDITIONS TO AVOID): Excessive heat, ignition sources. **INCOMPATIBILITY**: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: Smoke, Carbon Monoxide,

Carbon Dioxide.

HAZARDOUS POLYMERIZATION: Will not Occur.

**STABILITY**: Stable

## 11. TOXICOLOGICAL INFORMATION

Very low order of acute toxicity.

# **12. ECOLOGICAL INFORMATION**

Cleaned up material is not known to pose any significant ecological problems. Always comply with Federal, State and Local environmental regulations.

**DISPOSAL CONSIDERATIONS** Dispose as solid waste in sanitary landfill according to Federal, State and Local regulations. 14.

### **TRANSPORT INFORMATION**

NMF CLASSIFICATION: Class 60 - Item 156200 **DOT**: Not Regulated.

# **REGULATORY INFORMATION**

Review OSHA Std. for PPE in 29CFR 1910 Subpart I to ensure proper use for any applicable PPE.

# OTHER INFORMATION

The information in this MSDS was obtained from sources we believe are reliable. However, it is provided without any representation or warranty, expressed or implied, regarding accuracy or correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not

assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.

16.

15.

Page 4 of 4

13.